



Please fill out the product registration form online at: coralvue.com/register

12-Month Limited Warranty

Cora/We warrants to the original purchaser only that the Battery Badkup will be free from defects in material and workmanship under normal use or a period of one year provided that the product is installed and used properly and consistent with the product manual. No representation or warranty by any Cora/Wesalesperson, dealer, agent representative, employee or any other individual or entity, string or purporting to act on behalf of Cora/We, shall be binding upon Cora/Wesother than as expressly set forth herein. This limited warranty applies only to the original purchaser and is extremely additionable to exist a decrease on whose letters and it is disclosured by the limited of any absolute and wall the consistence of the subsolute and the subsolute and the consistence of the subsolute and the subsolu

Coral West warranty shall not apply, (ill oan y damaged Battery Backup that has been subjected to accident misuse, neglect, alteration acts of Conimproper handling immorper transport, improper storage improper user application improper restation improper testing or unauthorized repair, operation outside recommended parameters (as described in the applicable product manual for example, damage from saltwater spray or healt, power fluctuation or failure, subjection to abnormal physical or electrical stress, use of incompatible products non-approved power supplies connections, or similar circumstances (iii) to any Battery Backup where product been exposed towater or (iii) tho cosmetic problems or defects that result from normal wear and tear under ordinary use, and do not affect the performancer use of the product. Coral Nuës avairantie poblems or Coral Nue and identified by the Coral Nue, trade name or product identification logo affixed to the product. If you notice a problem with your Battery Backup, do not attempt to repair it yourself. Any attempts at self-repair shall void this limited warranty.

The Battery Badunjs designed to operate DC propeller pumps at 12 volts of Direct Qurrent (DC) in the event of a power outage. The Battery badung perate the DC pump in the event of a power outage. The nuntime that the pump will operate for while on battery power will depend upon many variables such as age and usage history of battery, the condition of your pump, the speed that you run at a while in battery badun prode, the number of pumps that you run off of one battery badun, or the number of batteries that you use to run one pump. These variables cannot be accurated you edicted and testing your runn and battery systems a critical or of resuriant the selfect of your analymnass into some outages.

There are many necessary conditions that aquarium livestock require to survive in a home aquarium which may not be met during periods where power is not being supplied to your anjurium equipment. As a result, automoperating in hattery backup mode maynot produce enough flowto prevent the death of aquarium livestock Coral/Ne shall not be held liable for the deaths of any aquarium livestock that occur while using the battery backup adving a power outageed rain yeight of time, under any condition. We strongly recomment that you consult an expert to determine the optimal battery backup and pumparangement to improve the likelihood of successfully maintaining your livestock during a power outage. We also recommend that you test your battery backup and pump system periodically to ensure that it is functioning optimally and to determine if it provides adequate flow homistariny our aquarium inhabitants in the event of a power outage. Finally were commend that your pumps used on the battery backup and pump system during a power outage be placed as high in the tank as possible, so as to disrupt the surface of the water and improve oxygen diffusion as much as possible. If the product develops a covered defect within the one-year period. Coral/New vill, at its option, either repair or replace the Battery Backup without drange, provided that the Battery Backup is returned furring the warranty period.

CORAUVEDISCLAINSALL OTHERWARRANTIESWHETHER ORAL OR WRITTEN LEGRESS OR IMPLED, TO THE FULLEST EXTENT ALLOWED BY APPLICABLE LAW. NO NIMPLED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY SHALL APPLY EXCEPT AS REQUIRED BY APPLICABLE LAW. CORALVUE DOES NOT AUTHORIZE ANY PERSON OR BUSINESS ENTITY, INCLUDING ITS AUTHORIZED DEALERS, TO CREATE FOR IT ANY OBLIGATIONS, LIABILITIES, OR OTHER WARRANTIES IN CONNECTION WITH THIS PRODUCT.

ALLWARRANTIESARE VOID IFTHERE IS DAMAGE TO THE BATTERY BACKUP THAT IS NOT A RESULT OF A DEFECT INTHE MATERIALS ORWORKMANSHIP. THE SOLE AND EXCLUSIVE REMEDY FOR ALL CLAIMST THAT YOU MAY HAVE ARISING OUT OF OR IN CONNECTION WITH YOU RUS OF THIS PRODUCT, WHETHER MADO CRESIPERES BY YOU OR AND THE PRESONALD WHETHER BASED IN CONTRACT OR TORTS HALL BE REPAIR OR REPLACEMENT OF THE PRODUCT IN NO EVENT WILL CORAL WE BE LIABLE TO YOU OR AN YOTHER PROTO PROPERTY OR TO THE PRODUCT IN THE PROPERTY OF THE DAMAGES ARISING OUT OF THE USE OR IN ABILITY OF TO USE THE PRODUCT (INCLUDING, WITHOUT LIMITATION DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION LLOSS OF INFORMATION OR ANY OTHER PECUNIARY LOSS DAMAGE TO YOUR AQUARIUM OR ANY YOU ARISING AND AND A SECRET OR AND A SECRET OR

Some states do not allow the exclusion or limitation of incidental or consequential chanages, so the above exclusions may not apply to you. Coral Nue's warranty is governed by the laws of the State of Louisiana, excluding its corollict of laws principles and excluding the provisions of the United Nations Convention on Contracts for the International Sale of Goods. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

TECHNICAL SUPPORT: This limited warranty is neither a service nor a support contract. Information about CoralVue's current support offerings and policies can be found at http://www.coralvue.com/support.

CONTENTS

- Battery Backup
- Battery Charger
- Installation Cables



OPERATION TIME

• 35 Hours Average*

This product contains a sealed lead acid battery MUST BE RECYCLED PROPERLY

SPECIFICATIONS

DC Charger: Input: 100V to 240V 50/60Hz | Output: 27V 600MA Main Unit DC: Output: 24V x 2.5A max | Input: 27V 1A max

Fuse: 250V 10A 5x20mm fast blow

Size and weight: 5.75in x 5in x 3.125in (WxLxH), 3.85lbs

OPERATION & MAINTENANCE


The battery backup should be maintained around 70° F to keep it in optimal condition. The life of the battery will also depend on the number of discharges that the unit has been cycled through. Every time the unit is cycled, the life of the battery and its capacity is reduced.

* Actual hours may vary due to operating conditions, pump draw and battery cycle times


BASIC SETUP


1 PUMP - 1 BATTERY BACKUP

Run one 24V DC pump off one IceCap Battery Backup for continuous operation up to 35 hours after the loss of power.*



Need help...Visit coralvue.com/support





SETUP SCENARIOS


Link Cable 200 PINE Y Cable 200 PINE Y Cable 200 PINE Y Cable

Two Pumps -One Battery Backup

You may run two 24V DC pumps off one Battery Backup using the provided cables as shown, but doing so will reduce the total run-time for each pump by approximately one-half.

Two Battery Backups -One Pump

In order to double the run-time of one 24V pump, connect it to two Battery Backups using the provided Y cable as illustrated.



文件大小: 120x95mm 工艺: 铜版纸, 包心折。

注: 红色虚线部分为说明书外轮廓大小, 不用印刷。